



**CMK系列快速接线端子**  
**CMK SERIES PUSH IN QUICK-CONNECTORS**

Material of connectors shell: Transparent polycarbonate

Material of actuating levers: Polyamide Pom

Material of conductive parts: Thinned copper

Material of contact springs: AISI 301 stainless steel

Rated voltage(V): 450V AC

Rated current(A): 32A







Connection capacity: 0.75-2.5mm<sup>2</sup>

Type of electric connection: Equipotential

Working temperature: -40°C to 105°C

Strip length: 13mm/0.51 Inch



Product Code	Connector type	No.of circuits	Rigid wire mm <sup>2</sup>	Flexible wire mm <sup>2</sup>	Volt (V)	Ampere (A)	Un 	Un 
CMK-612		2	1.0→2.5	0.75→2.5	450 V	32 A	100	6000
CMK-613		3					100	4000
CMK-614		4					100	4000
CMK-615		5					100	4000



CMK-612








CMK-613



CMK-614



CMK-615

Product Code	Connector type	No.of circuits	Rigid wire mm <sup>2</sup>	Flexible wire mm <sup>2</sup>	Volt (V)	Ampere (A)	Un 	Un 
CMK-101		1-1	0.5→2.5	1.0→2.5	450 V	24 A	100	6000
CMK-112		1-2					100	4000
CMK-201		1-1					50	2000