



**CMK系列快速接线端子**  
**CMK SERIES PUSH IN QUICK-CONNECTORS**

Material of connectors shell: Transparent polycarbonate

Material of actuating levers: Polyamide pom

Material of conductive parts: Thinned copper

Material of contact springs: AISI 301 stainless steel

Rated voltage(V): 450V AC

Rated current(A): 32A

Connection capacity: 0.2-4mm<sup>2</sup>

Type of electric connection: Equipotential

Working temperature: -40°C to 105°C

Strip length: 11mm/0.43 Inch



Product Code	Connector type	No.of circuits	Flexible wire mm <sup>2</sup>	Rigid wire mm <sup>2</sup>	Volt (V)	Ampere (A)	Product size (mm)	Un
CMK-632		2	0.2→2.5	0.2→4	450 V	32 A	15.5×19.2×10.3	6000
CMK-633		3					21.8×19.2×10.3	4000
CMK-634		4					28.1×19.2×10.3	4000
CMK-635		5					34.4×19.2×10.3	2000



CMK-632

CMK-633

CMK-634

CMK-635

Product Code	Connector type	No.of circuits	Flexible wire mm <sup>2</sup>	Rigid wire mm <sup>2</sup>	Volt (V)	Ampere (A)	Product size (mm)	Un
CMK-662		2	0.2→4	0.2→6	600 V	41 A	15.8×21×11.6	4000
CMK-663		3					22.1×21×11.6	2000
CMK-665		5					34.7×21×11.6	2000



CMK-662

CMK-663

CMK-665