



CMK系列快速接线端子
CMK SERIES PUSH IN QUICK-CONNECTORS

Material of connectors shell: Transparent polycarbonate

Material of actuating levers: Polyamide pom

Material of conductive parts: Thinned copper

Material of contact springs: AISI 301 stainless steel

Rated voltage(V): 450V AC

Rated current(A): 24A

Connection capacity: 0.08-4mm²

Type of electric connection: Equipotential

Working temperature: -20°C to 85°C

Strip length: 11mm/0.43 Inch



Product Code	Connector type	No. of circuits	Flexible wire mm ²	Color	Volt (V)	Ampere (A)	Un	Un
CMK211-1		1-1	0.5→1.0 1.0→1.5 1.5→2.5 2.5→4.0	transparent red blue yellow	450 V	24 A	100	4000
CMK211-2		1-2	0.5→1.0 1.0→1.5 1.5→2.5 2.5→4.0	transparent red blue yellow			100	4000
CMK212-2		2-2	0.5→1.0 1.0→1.5 1.5→2.5	transparent red blue			50	2000
CMK212-4		2-4	0.5→1.0 1.0→1.5 1.5→2.5	transparent red blue			50	2000



CMK-211-1



CMK-211-2



CMK-212-2



CMK-212-4

